



SATA GmbH & Co. KG • Postfach 1828 • 70799 Kornwestheim

To Whom It May Concern

Unser Zeichen

G. Drakos

Telefon

+49 (71 54) 8 11-4 72

Telefax

+49 (71 54) 8 11-1 90

eMail

georg.drakos@sata.com

Datum

8. November 2010

It is our pleasure to confirm that the following SATA spray guns do comply with HVLP mandates; namely that they show maximum 10 psi air cap pressure at recommended spray gun inlet pressure highlighted in the operating manuals. The transfer efficiency of all listed SATA HVLP spray guns is larger 65 % provided the spray gun is set-up by the user with the recommended inlet pressure and spray distance shown in the operating manuals.

SATAjet® B NR 95	maximum spray gun inlet pressure:	43 psi
SATAjet® K NR 95	maximum spray gun inlet pressure:	43 psi
SATAminijet® NR	maximum spray gun inlet pressure:	43 psi
SATAminijet® 2 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 3 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 4 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP DIGITAL® 2	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® K3™ HVLP	maximum spray gun inlet pressure:	36 psi
SATAjet® K3™ HVLP DIGITAL®	maximum spray gun inlet pressure:	36 psi
SATA® KLC™ HVLP	maximum spray gun inlet pressure:	29 psi
SATA® LM™ 2000 B HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 H HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 K HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LP™ jet K3™ HVLP	maximum spray gun inlet pressure:	58 psi
SATA® LP™ jet K3™ HVLP ROB™	max. round air inlet pressure:	42 psi
	max. flat air inlet pressure:	48 psi
SATAjet® 90-2 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 1000 K™ HVLP	maximum spray gun inlet pressure:	36 psi
SATAjet® 100 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 1000 B HVLP	maximum spray gun inlet pressure:	29 psi

SATA GmbH & Co. KG
R&D Department


i. V. Dr. Ewald Schmon


i. V. Jörg Göttling

Hausanschrift:
Domertalstr. 20 • 70806 Kornwestheim
Telefon +49 71 54 8 111-0
Fax Verkauf -196 • Export -194 • Einkauf -193
E-Mail: info@sata.com
Internet: www.sata.com

Bankverbindungen:
Commerzbank Ludwigsburg (BLZ 604 400 73) Kto. 7 322 001
BIC: COBADEFFXXX • IBAN: DE85 6044 0073 0732 2001 00
Kreissparkasse Ludwigsburg (BLZ 604 500 50) Kto. 25 669
BIC: SOLADES1LBG • IBAN: DE10 6045 0050 0000 0256 69
BW-Bank Ludwigsburg (BLZ 600 501 01) Kto. 7 832 500 403
BIC: SOLADEST • IBAN: DE04 6005 0101 7832 5004 03

Kommanditgesellschaft mit Sitz in Kornwestheim
Registergericht: Stuttgart HRA 202151
Persönlich haftende Gesellschafterin:
SATA Verwaltungs-GmbH, Kornwestheim, HRB 202857
Geschäftsführer: Albrecht Kruse, Stuttgart
USt-IdNr.: DE 146132518

